

**CLAIMS** (no amendments)

Claims 1-37 (Canceled)

38. **(Currently amended)** An antenna comprising:  
an element; and wherein  
the element is formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, the PCB is apertured at a location that is adjacent to the element and between an I-, L-, or F-shaped conductor pattern and a ground plane area, and the conductor patterns are in stacked relation and interconnected through the PCB.
39. **(Currently amended)** An antenna according to claim 38, wherein the ground plane comprises ~~comprising:~~  
~~an element, wherein the element is formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, and the conductor patterns are in stacked relation and interconnected through the PCB; and~~  
an antenna ground plane comprising a plurality of vias connecting ground plane regions on respective PCB layers.
40. **(Canceled)** ~~An antenna according to claim 39, wherein the PCB is apertured adjacent to the element.~~
41. (Canceled)
42. (Canceled)
43. (Canceled)

44. **(Currently amended)** A mobile phone including an antenna disposed therein, said antenna comprising an element formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, wherein the conductor patterns are in stacked relation and interconnected through the PCB, and wherein the PCB is apertured at a location that is adjacent to the element and between an I-, L-, or F-shaped conductor pattern and a ground plane area.
45. (Canceled)
46. **(Currently amended)** A mobile phone according to claim 44, wherein the ground plane comprises ~~including an antenna disposed therein, said antenna comprising (a) an element formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, and (b) an antenna ground plane comprising a plurality of vias connecting ground plane regions on respective PCB layers; wherein the conductor patterns are in stacked relation and interconnected through the PCB, and wherein the PCB is apertured adjacent to the element.~~
47. (Canceled)
48. **(Currently amended)** A mobile phone according to claim 44, including an antenna ~~disposed therein, said antenna comprising an element formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, wherein the conductor patterns are in stacked relation and interconnected through the PCB, wherein interconnection of the conductor patterns is from the conductor patterns through the at least one buried layer, and wherein the~~

interconnection is by vias extending through the at least one buried layer of the PCB.

49. **(Currently amended)** An antenna structure, comprising:
- a substrate having a footprint;
- an antenna trace having an I-, L-, or F-shape and a perimeter formed on a face of said substrate proximate a ground plane of said substrate and said perimeter being substantially co-planar with said face, wherein said substrate has a predetermined radio frequency loss associated therewith; and
- a low-loss region extending through said substrate, wherein said low-loss region is an opening located within said footprint that extends transverse to and intersects a plane of said face, and said low-loss region located between said antenna trace and said ground plane, wherein said low-loss region has a radio frequency loss less than said radio frequency loss associated with said substrate, and wherein said low-loss region is located outside of said perimeter of said antenna trace.
50. (Previously presented) The antenna structure recited in claim 49 further including a plurality of said low-loss regions.
51. (Previously presented) The antenna structure recited in claim 50 wherein each of said low-loss regions is separated by a portion of said substrate.
52. (Previously presented) The antenna structure recited in claim 49 wherein said low-loss region comprises air.

53. (Previously presented) The antenna structure recited in claim 49 wherein said antenna trace includes antenna traces located on opposing surfaces of said substrate and connected by a via.
54. (Previously presented) The antenna structure recited in claim 49 wherein said substrate is comprised of a high loss material.
55. (**Currently amended**) A method of manufacturing an antenna structure, comprising:  
forming an antenna trace having an I-, L-, or F-shape and a perimeter formed on a face of a substrate having a footprint proximate a ground plane of said substrate and said perimeter being substantially co-planar with said face, wherein said substrate has a predetermined radio frequency loss associated therewith; and  
creating a low-loss region extending through said substrate and located between said antenna trace and said ground plane, wherein said low-loss region is an opening located within said footprint that extends transverse to and intersects a plane of said face, and wherein said low-loss region has a radio frequency loss less than said radio frequency loss associated with said substrate, and wherein said low-loss region is located outside said perimeter of said antenna trace.
56. (Previously presented) The method recited in claim 55 wherein said creating includes creating a plurality of low-loss regions.

57. (Previously presented) The method recited in claim 55 wherein said creating includes creating a plurality of low-loss regions separated by a portion of said substrate.
58. (Previously presented) The method recited in claim 55 wherein said substrate is comprised of a high-loss material.
59. (Previously presented) The method recited in claim 55 wherein said creating includes creating a low-loss region comprising air.
60. (Previously presented) The method recited in claim 55 wherein said forming includes forming antenna traces located on opposing surfaces of said substrate interconnected by a via extending through said substrate.
61. **(Currently amended)** A printed circuit board (PCB), comprising:  
a substrate having a footprint and a ground plane and conductive traces formed thereon, wherein said substrate has a predetermined radio frequency loss associated therewith; and  
an antenna structure, including:  
an antenna trace having an I-, L-, or F-shape and a perimeter formed on a face of a substrate proximate a ground plane of said substrate and said perimeter being substantially co-planar with said face, wherein said substrate has a predetermined radio frequency loss associated therewith; and  
a low-loss region extending through said substrate and located between said antenna trace and said ground plane, wherein said low-loss region is an opening located within said footprint that extends transverse to and

intersects said face, and wherein said low-loss region has a radio frequency loss less than said radio frequency loss associated with said substrate, and wherein said low-loss region is located outside said perimeter of said antenna trace.

62. (Previously presented) The PCB recited in claim 61 wherein said substrate is comprised of a high-loss material.
63. (Previously presented) The PCB recited in claim 61 wherein said low-loss region includes a plurality of low-loss regions separated by a portion of said substrate.
64. (Previously presented) The PCB recited in claim 61 wherein said substrate has a footprint, and said low-loss region is an opening located within a said footprint of said substrate.
65. (Previously presented) The PCB recited in claim 64 wherein said low-loss region includes a low-loss material comprising air.
66. (Previously presented) The PCB recited in claim 61 wherein said antenna trace includes antenna traces located on opposing surfaces of said substrate interconnected by a via extending through said substrate.
67. (**Currently amended**) An antenna structure, comprising:  
an antenna trace having an I-, L-, or F-shape and being formed on a substrate proximate a ground plane of said substrate, wherein said substrate has a footprint and a predetermined radio frequency loss associated therewith;  
and

a low-loss region extending through said substrate and located between said antenna trace and said ground plane, wherein said low-loss region is an opening located within said footprint that extends transverse to and intersects a plane of said face, and wherein said low-loss region has a radio frequency loss less than said radio frequency loss associated with said substrate, and said antenna trace does not overlap said low-loss region.

68. **(Currently amended)** An antenna structure, comprising:  
a planar antenna trace having an I-, L-, or F-shape and being formed on a substrate;  
a ground plane formed on said substrate, wherein a plane of said substrate on which said planar antenna is located is co-planar or parallel with a plane of said substrate on which said ground plane is located, and said ground plane is non-overlapping with said planar antenna trace; and  
an insulation region extending through said substrate and located between said planar antenna trace and said ground plane.
69. (Previously presented) The antenna structure recited in claim 68, wherein said planar antenna trace is a first planar antenna trace and said antenna structure further includes a second planar antenna trace located on an opposing, parallel surface of said substrate and said first and second planar antenna traces are interconnected by a via extending through said substrate.
70. (Previously presented) The antenna structure recited in claim 68 wherein said insulation region includes a plurality of insulation regions.

71. (Previously presented) The antenna structure recited in claim 70 wherein each of said insulation regions are separated by a portion of said substrate.
72. (Previously presented) The antenna structure recited in claim 68 wherein said insulation region is an opening that extends through said substrate and an insulator of said insulation region is air.
73. (Previously presented) The antenna structure recited in claim 68 wherein said substrate is a lossy substrate.
74. (**Currently amended**) A method of manufacturing an antenna structure, comprising:  
forming a planar antenna trace on a substrate, the trace having an I-, L-, or F-shape;  
forming a ground plane on said substrate, wherein a plane of said substrate on which said planar antenna is located is co-planar or parallel with a plane of said substrate on which said ground plane is located, and said ground plane is non-overlapping with said planar antenna trace; and  
creating an insulation region extending through said substrate and located between said planar antenna trace and said ground plane.
75. (Previously presented) The method recited in claim 74, wherein said planar antenna trace is a first planar antenna trace and said antenna structure further includes a second planar antenna trace located on an opposing, parallel surface of said substrate and said first and second planar antenna traces are interconnected by a via extending through said substrate.



76. (Previously presented) The method recited in claim 74, wherein said creating includes creating a plurality of insulation regions.
77. (Previously presented) The method recited in claim 74, wherein said creating a plurality of insulation regions includes creating a plurality of insulation regions separated by a portion of said substrate.
78. (Previously presented) The method recited in claim 74, wherein said creating an insulation region includes creating an opening that extends through said substrate and wherein an insulator of said insulation region is air.
79. (Previously presented) The method recited in claim 74, wherein said forming includes forming antenna traces located on opposing surfaces of said substrate interconnected by a via extending through said substrate.
80. **(Currently amended)** A printed circuit board (PCB), comprising,  
a substrate having  
a ground plane and conductive traces formed thereon; and  
a planar antenna structure, including: an antenna trace having an I-, L-, or F-shape and being formed on said substrate; said planar ground plane formed on said substrate, wherein a plane of said substrate on which said planar antenna is located is co-planar or parallel with a plane of said substrate on which said ground plane is located, and said ground plane is non-overlapping with said antenna trace; and  
an insulation region extending through said substrate and located between said antenna trace and said ground plane.

81. (Previously presented) The PCB recited in claim 80, wherein said planar antenna trace is a first planar antenna trace and said antenna structure further includes a second planar antenna trace located on an opposing, parallel surface of said substrate and said first and second planar antenna traces are interconnected by a via extending through said substrate.
82. (Previously presented) The PCB recited in claim 80, further including electrical components mounted on said substrate and interconnected between at least one of said conductive traces and said ground plane to form an operative circuit.
83. (Previously presented) The PCB recited in claim 80, wherein said insulation region includes a plurality of insulation regions separated by a portion of said substrate.
84. (Previously presented) The PCB recited in claim 80, wherein said insulation region is an opening that extends through said substrate and an insulator of said insulation region is air.
85. **(Currently amended)** An antenna structure, comprising:  
an antenna substrate having a planar surface, said antenna substrate having a predetermined radio frequency loss associated therewith;  
a planar antenna trace having an I-, L-, or F-shape, being formed on said planar surface, and extending along and adjacent an edge of said planar surface;  
a ground plane formed on said antenna substrate, wherein said ground plane is non-overlapping with said planar antenna trace; and  
a low-loss region located between said planar antenna trace and said ground plane, said low-loss region having a longitudinal axis extending along only a

portion of and adjacent said edge, and having a radio frequency loss less than said predetermined radio frequency loss.

86. (Previously presented) The antenna structure recited in claim 85, wherein said low-loss region is non-overlapping with said planar antenna trace.
87. (Previously presented) The antenna structure recited in claim 86, wherein said ground plane is a planar ground plane and is located on said planar surface and is co-planar with said planar antenna trace.
88. (Previously presented) The antenna structure recited in claim 85 further including a plurality of said low-loss regions, wherein each of said low-loss regions is separated by a portion of said substrate and each of said plurality is non-overlapping with said planar antenna trace.
89. (Previously presented) The antenna structure recited in claim 85 wherein said low-loss region comprises air.
90. (Previously presented) The antenna structure recited in claim 85 wherein said planar antenna trace comprises a first portion that extends in one direction along said edge and a second portion that extends in an opposite direction along said edge.
91. (Previously presented) The antenna structure recited in claim 85 wherein said low-loss region is an opening that extends through a thickness of said substrate.
92. (**Currently amended**) A method of manufacturing an antenna structure, comprising:

providing an antenna substrate having a planar surface, said antenna substrate  
having a predetermined radio frequency loss associated therewith,  
forming a planar antenna trace on said planar surface along and adjacent an edge of  
said planar surface, the antenna trace having an I-, L-, or F-shape;  
placing a ground plane on said antenna substrate, wherein said ground plane is non-  
overlapping with said planar antenna trace; and  
creating a low-loss region between said planar antenna trace and said ground plane,  
said low-loss region having a longitudinal axis extending along only a  
portion of and adjacent said edge, said low-loss region having a radio  
frequency loss less than said predetermined radio frequency loss.

93. (Previously presented) The method recited in claim 92, wherein said low-loss region is non-overlapping with said planar antenna trace.
94. (Previously presented) The method recited in claim 92, wherein said ground plane is a planar ground plane formed on said planar surface and co-planar with said planer antenna trace.
95. (Previously presented) The method recited in claim 92 wherein said creating includes creating a plurality of low-loss regions, wherein each of said low-loss regions is separated by a portion of said substrate and each of said plurality is non-overlapping with said planar antenna trace.
96. (Previously presented) The method recited in claim 92 wherein said creating includes creating a low-loss region comprising air.

97. (Previously presented) The method recited in claim 92 wherein said forming includes forming first and second portions of said planar antenna trace where said first portion extends in one direction along said edge and the second portion extends in an opposite direction along said edge.

98. (Previously presented) The method recited in claim 92 wherein said creating said low-loss region comprises forming an opening that extends through a thickness of said substrate.

Claims 99-118 (Canceled)

119. (**Currently amended**) An antenna according to claim 38, comprising:  
~~an element; and wherein~~  
~~the element is formed from conductor patterns on a plurality of layers including at~~  
~~least one buried layer of a multilayer PCB, and the conductor patterns are in~~  
~~stacked relation and interconnected through the PCB, and wherein~~  
interconnection of the conductor patterns is from the conductor patterns  
through the at least one buried layer, and wherein the interconnection is by  
vias extending through the at least one buried layer of the PCB.

120. (Previously presented) An inverted F-antenna comprising:  
an element, and wherein  
the element is formed from conductor patterns on a plurality of layers including at  
least one buried layer of a multilayer PCB, and the conductor patterns are in  
stacked relation and interconnected through the PCB, and the conductor  
patterns comprise an F-shaped conductor pattern on a first layer of the PCB

and an I-, L- or F-shaped conductor pattern on the or each other layer, wherein the or each I-, L- or F-shaped conductor pattern comprises an upright substantially coextensive with an upright of the F-shaped conductor pattern on the first layer, the or each I-, L- or F-shaped conductor pattern extends along the edge of the PCB, and wherein the PCB is apertured between the upright of the F-shaped conductor pattern and a ground plane area.

121. (Previously presented) An antenna comprising:  
an element; and wherein  
the element is formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, the conductor patterns are in stacked relation and interconnected through the PCB, and the PCB is apertured between an upright of an F-shaped conductor pattern and a ground plane area.
122. (Previously presented) A mobile phone including an inverted F-antenna comprising an element formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, wherein the conductor patterns are in stacked relation and interconnected through the PCB, and comprise an F-shaped conductor pattern on a first layer of the PCB and an I-, L- or F-shaped conductor pattern on the or each other layer, wherein the or each I-, L- or F-shaped conductor pattern comprises an upright substantially coextensive with the upright of the F-shaped conductor pattern, wherein the or each I-, L- or F-shaped conductor pattern

extends along the edge of the PCB, and wherein the PCB is apertured between the upright of the F-shaped conductor pattern and a ground plane area.

123. (Previously presented) A mobile phone including an antenna comprising an element formed from conductor patterns on a plurality of layers including at least one buried layer of a multilayer PCB, wherein the conductor patterns are in stacked relation and interconnected through the PCB, and wherein the PCB is apertured between an upright of an F-shaped conductor pattern and a ground plane area.